



Cable ID: PCF5-10CC-0500-S

Date / Time: 07/04/2019 03:23:19 PM

Headroom 11.0 dB (NEXT 36-78)

Test Limit: TIA Cat 5e Channel

Cable Type: Cat 5e F/UTP

NVP: 69.0%

Software Version: V6.2 Build 1

Limits Version: V7.2

Calibration Start Date:

Main (Module): 12/03/2018

Remote (Module): 12/03/2018

Test Summary: PASS

Model: DSX-8000


Main S/N: 1820302

Remote S/N: 1824298

Main Adapter: DSX-CHA804


Remote Adapter: DSX-CHA804

Length (ft), Limit 328	[Pair 36]	17
Prop. Delay (ns), Limit 555	[Pair 12]	26
Delay Skew (ns), Limit 50	[Pair 12]	1
Resistance (ohms)	[Pair 12]	3.12
Insertion Loss Margin (dB)	[Pair 36]	21.9
Frequency (MHz)	[Pair 36]	100.0
Limit (dB)	[Pair 36]	24.0




Wire Map (T568B)

PASS





Insertion Loss (dB)





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	36-78	36-78	45-78	36-78
NEXT (dB)	11.4	11.0	14.8	11.4
Freq. (MHz)	60.3	63.5	100.0	66.8
Limit (dB)	33.9	33.5	30.1	33.1
Worst Pair	36	36	78	36
PS NEXT (dB)	13.8	13.1	15.4	13.8
Freq. (MHz)	60.3	63.5	100.0	69.8
Limit (dB)	30.9	30.5	27.1	29.8





PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45	45-36	36-45	45-36
ACR-F (dB)	31.3	31.3	31.4	31.4
Freq. (MHz)	75.3	75.3	75.8	75.8
Limit (dB)	19.9	19.9	19.8	19.8
Worst Pair	45	78	45	45
PS ACR-F (dB)	31.2	31.0	32.9	33.3
Freq. (MHz)	1.0	1.0	77.5	76.0
Limit (dB)	54.4	54.4	16.6	16.8



N/A	MAIN	SR	MAIN	SR
Worst Pair	12-78	45-78	45-78	36-78
ACR-N (dB)	22.0	18.7	36.9	29.1
Freq. (MHz)	2.4	1.8	100.0	66.8
Limit (dB)	53.8	56.4	6.1	13.8
Worst Pair	78	78	78	36
PS ACR-N (dB)	22.4	20.1	37.5	31.8
Freq. (MHz)	2.4	1.8	100.0	69.8
Limit (dB)	50.8	53.4	3.1	10.0



N/A	MAIN	SR	MAIN	SR
Worst Pair	45	45	45	12
RL (dB)	4.0	4.5	7.6	7.1
Freq. (MHz)	11.1	10.6	75.0	74.3
Limit (dB)	17.0	17.0	11.3	11.3



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	2.5GBASE-T	ATM-25
ATM-51	ATM-155	100VG-AnyLan
TR-4	TR-16 Active	TR-16 Passive